

# 60X12FT 52hp, DELUXE CRUISER SAILAWAY

Live aboard  
**£43,895** Inc VAT at 0%  
 Leisure  
**£50,874** Inc VAT

**Hull Specification**

*Hull, with window apertures, door openings, Stainless Steel water tank, fuel tank, gas locker, engine beds, deck fittings etc. See more below.*

|                         |  |
|-------------------------|--|
| <b>Fuel tank</b>        | Steel integral fuel tank approximately 80gallon, with feed, return, filler and vent. |
| <b>Water Tank</b>       | Approximately 110gallon, Stainless Steel Water tank. No treatment needed.            |
| <b>Gas Locker</b>       | Self-draining and vented locker. Space for 2 x 13kg gas Bottles                      |
| <b>Weed Hatch</b>       | Complete with quick release cover.   |
| <b>Deck Fittings</b>    | 1x rope stud fwd, 2x bollards aft & centre mooring ring. Pole and plank rack.        |
| <b>Decks</b>            | All self-draining.   |
| <b>Window Apertures</b> | Chrome single glazed windows and portholes fitted.                                   |
| <b>Engine Beds</b>      | To suit Canaline engine.   |
| <b>Stern Tube</b>       | Fitted to suit 35mm Vetus water cooled type. No greasing needed until service.       |
| <b>Engine Cooling</b>   | Skin tank with 1" ½ take offs and drain.   |
| <b>Rubbing Stakes</b>   | 1 full length with quarter fore & aft. Welded top & bottom.                          |
| <b>Handrail</b>         | Integral handrails on coach roof With drainage points.                               |

**Steel Specification**

|                            |  |
|----------------------------|--|
| <b>Base Plate</b>          | 10mm                                   |
| <b>Hull Sides</b>          | 6mm                                    |
| <b>Cabin Sides</b>         | 5mm                                    |
| <b>Coach Roof</b>          | 4mm on 25mm x 25mm rolled box section. |
| <b>Bulk Heads</b>          | 4mm                                    |
| <b>Knees and Stringers</b> | 50 x 50 x 5mm angle.                   |
| <b>Floor Bearers</b>       | 75 x 50 8mm angle.                     |
| <b>Rubbing Strakes</b>     | 50 x 12mm half round.                  |
| <b>Bulk Head Ribs</b>      | 45 x 5mm flat.                         |

**Principal Features**

|                                |   |
|--------------------------------|---|
| <b>Engine</b>                  | Canaline 52hp Engine. Matched Gear Box fully installed. Standard instrumentation.                 |
| <b>Bow Thruster</b>            | Vetus BOW95/12 Thruster   |
| <b>Steering</b>                | Tiller steering   |
| <b>Ballast</b>                 | Adequate ballast is installed. Into a bitumen prepared base.                                      |
| <b>Insulation</b>              | Battened out and fully spray foam insulated.  |
| <b>Floor</b>                   | Treated 18mm WBP plywood floor, fitted on to tanalised floor Bearers.                             |
| <b>Windows &amp; Portholes</b> | Chrome polished Single Glazed All windows/ portholes vented.                                      |
| <b>Doors, Stern</b>            | Twin steel doors to the rear with sliding hatch.  |
| <b>Doors, Bow</b>              | Steel front doors, half glazed.   |
| <b>Doors, Side</b>             | One set of side doors fitted.   |
| <b>Other Features</b>          | 4 x 2.5kg Anodes fitted. Chrome tiller and pin. Metroplex plywood aft deck. Automatic bilge pump. |

|                           |   |
|---------------------------|---|
| <b>External Paintwork</b> | Primed with Zinc Phosphate primer. Hull Is blackened up to the rubbing strake. Colour: Holding primer only. |
|---------------------------|---|



**ALL SAIL AWAYS SOLD THROUGH NOTTINGHAM BOAT CO ARE WATER TESTED ON SITE.**

